



Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

Article number: 03.9901-53xx.x / 7053xx

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket & Services GmbH

Sodener Straße 9

D-65824 Schwalbach am Taunus

Tel: +49-69-7603-11 Fax: +49-69-761061

Further information obtainable from:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

Emergency telephone number:

For emergencies related to Hazardous Substances including poisoning call:

Israel Poison Information Center at Rambam Health Care Campus: 04-854-1900 medical advice 24-

hour.

For inquiries on working with Hazardous Substances call:

Institute for Safety and Hygiene: 5266444-03

2 Hazards identification

Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

Label elements

GHS label elements Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-

tetraoxahexadecan-1-ol

Eye Dam. 1, H318; Acute Tox. 5, H313

Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 %

Eye Irrit. 2; H319: 20 % ≤ C < 30 %

(Contd. on page 2)

- IL





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

	(Contd. (of page 1)
111-46-6	2,2'-oxybisethanol	<10%
	Acute Tox. 4, H302	
111-77-3	2-(2-methoxyethoxy)ethanol	<3%
	Repr. 2, H361; Flam. Liq. 4, H227	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air or oxygen; call for doctor.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx.

Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Keep out of the reach of children.

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

Store in dry conditions.

This product is hygroscopic.

Keep container tightly sealed.

Storage class according to TRGS 510: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection:

If occupational exposure limits are exceeded, use breathing mask (filter type A). Wear self-contained breathing apparatus in case of danger of oxygen displacement.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 3)

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

Physical and chemical properties	
Information on basic physical and che	emical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	10 (FMVSS 116)
Change in condition	
Melting point/freezing point:	<-70 °C
Initial boiling point and boiling range	e: >245 °C (FMVSS 116)
Flash point:	>130 °C (ASTM D 7094 (closed cup))
Flammability (solid, gas):	Not applicable.
Ignition temperature:	230 °C (DIN 51794)
Decomposition temperature:	>360 °C (DSC)
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	1.5 Vol %
Vapour pressure at 20 °C:	<10 hPa
Density at 20 °C:	1.04-1.07 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.

(Contd. on page 5)





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 4)

Viologia.	(>	orita. or page
Viscosity:	No. 4 of other months and	
Dynamic:	Not determined.	
Kinematic at 20 °C:	14.5-17 mm²/s (FMVSS 116)	
Solvent content:		
Organic solvents:	28.8 %	
Water:	0.1 %	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

Information on toxicological effects Acute toxicity

-		
LD/LC50 values	relevant for	classification:

Reaction	on mas	s of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)
111-46-	6 2,2'-	oxybisethanol
Oral	LD50	>5,000 mg/kg (rat)

Dermal	LD50	>5,000 mg/kg (rabbit)
		-,,

111-77-3 2-(2-methoxyethoxy)ethanol

Oral	LD50	>5,000 mg/kg (mouse) (OECD 401)
Dermal	LD50	>5.000 mg/kg (rabbit) (OECD 402)

Primary irritant effect:

Skin corrosion/irritation No irritant effect.

Serious eye damage/irritation No irritating effect.

Respiratory or skin sensitisation No sensitising effects known.

(Contd. on page 6)





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 5)

12 Ecological information

Toxicity

•	
Aquatic toxic	city:
LC50	>100 mg/L (fish) (DIN 38412)
Reaction ma	ss of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol
EC50	>100 mg/l (Algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish) (DIN 38412 96 h)
111-46-6 2,2	-oxybisethanol
EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia) (DIN 38412 T.11)
LC50	>100 mg/L (fish) (96 h)
111-77-3 2-(2	2-methoxyethoxy)ethanol
EC50	>100 mg/l (Algae)
	>100 mg/l (daphnia)
LC50 (static)	>100 mg/L (fish)

Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment Not applicable.

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation Must be specially treated adhering to official regulations.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 7)

11





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 6)

Transport information		
UN-Number ADR, ADN, IMDG, IATA	Void	
UN proper shipping name ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
Packing group ADR, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Anno Marpol and the IBC Code	ex II of Not applicable.	
UN "Model Regulation":	Void	

15 Regulatory information

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The information in the sheet was written based on the best knowledge and experience currently available.

Relevant phrases

H227 Combustible liquid.

H302 Harmful if swallowed.

H313 May be harmful in contact with skin.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Gefahrstoffmanagement Konzern ate.sicherheit@contiautomotive.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 8)





Printing date 11.02.2020 Version number 7 Revision: 31.01.2020

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 7)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 4: Flammable liquids – Category 4 Acute Tox. 4: Acute toxicity - oral – Category 4 Acute Tox. 5: Acute toxicity - dermal – Category 5

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Repr. 2: Reproductive toxicity - Category 2

Sources

http://echa.europa.eu/information-on-chemicals/cl-inventory

http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances

http://www.reach-clp-biozid-helpdesk.de/de/Downloads/CLP-VO/CLP_VO_Anhang_VI_Tabelle_3_2.pdf

http://www.safeworkaustralia.gov.au/

IL

^{*} Data compared to the previous version altered.